



Castrol MAGNATEC Professional S1 5W-30

CLINGING MOLECULES PROTECT FROM THE START

Description

Castrol MAGNATEC Professional's intelligent molecules protect from the moment you start. They cling to the engine like a magnet providing an extra layer of protection, dramatically reducing* engine wear.

Castrol MAGNATEC Professional's unique formulation delivers protection you can see, hear and feel.

It is now certified CO2 neutral according to the highest global standards. Engineered with Micro-Filtration in order to meet Castrol Professional's new quality standard and verified using Castrol's new Optical Particle Measurement System (OPMS) to guarantee product quality.

Castrol MAGNATEC Professional. Instant Protection From The Moment You Start.

** As tested against the industry Sequence IVA wear test.*

Application

Castrol MAGNATEC Professional S1 5W-30 is suitable for use in automotive gasoline and diesel engines where the manufacturer recommends an ACEA C2 5W-30 lubricant.

Castrol MAGNATEC Professional S1 5W-30 is suitable for use in FIAT vehicles where a 5W-30 lubricant that Meets - Fiat 9.55535-S1 specification.

Advantages

Castrol MAGNATEC Professional's Intelligent Molecules:

- Cling to critical engine parts when the oil drains down
- Cling to your engine forming an extra layer that protects during start up and beyond;
- Bond to metal surfaces to make engine parts more resistant to wear;
- Are combined with synthetic technology to provide increased protection in high and low temperature applications;
- Provide continuous protection for all driving conditions, styles and temperatures;
- Deliver superior performance under extreme cold start up conditions

Typical Characteristics

Name	Method	Units	Castrol MAGNATEC Professional S1 5W-30
Density @ 15C, Relative	ASTM D4052	g/ml	0.850
Appearance	Visual	-	Slight haze possible
Viscosity, Kinematic 100C	ASTM D445	mm ² /s	10.3
Viscosity, CCS -30C	ASTM D5293	mPa.s (cP)	5500
Flash Point PMCC	ASTM D93	°C	209
Viscosity, Kinematic 40C	ASTM D445	mm ² /s	60
Viscosity Index	ASTM D2270	None	159
Ash, Sulphated	ASTM D874	% wt	0.7
Pour Point	ASTM D97	°C	-46

Product Performance Claims

ACEA C2
API SN
Meets - Fiat 9.55535-S1

Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

Castrol MAGNATEC Professional S1 5W-30
23 Nov 2017
Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol (UK) Limited, PO BOX 354, Chertsey Road, Sunbury On Thames, Middlesex, TW16 9AW
Orders/Enquiries: 0345 6008125 Technical Enquiries: 0345 082 1719 BP (Ireland) Ireland Orders/Enquiries: 1850 930 3942 Ireland Technical Enquiries: 1800 509 353
www.castrol.com/uk